



LUXOMAT® Indoor 180-M-2C



Remote controllable



TECHNICAL DATA

- 230V~ ±10%
- 180°
- max. 10.00 m
- IP20 / Class II / C€
- L87 x W87 x D61 mm
- 25°C to +50°C
- UV- and shock-resistant Polycarbonate
- IR-PD, IR-PD-Mini
- Channel 1 (control the lighting)**
- 2300 W, cosφ = 1; 1150 VA, cosφ = 0.5
- 15 sec. - 30 min. or impulse
- 5 - 2000 Lux
- Channel 2 (control HVAC)**
- Dry contact type NO, 3A, 230 V, cosφ = 1
- Alarm impulse, impulse or 5 - 120 min.

PRODUCT INFORMATION

- Remote controllable occupancy detector LUXOMAT® Indoor 180-M-2C as Master as wall switch with 180° detection area
- Combinable with coverings in five different colours
- For the combination with switches of leading manufacturers the enclosed additional intermediate frame can be used
- 2 switching channels, one to switch the lighting, the second to switch other loads e.g. HVAC by potential free relay of the detector
- The connection of an unlimited number of slaves is possible!
- Version IP20 and IP54 (only European version – for moisture-proofs, garages, cellar steps)
- Light measuring: mixed light – artificial and daylight (occupancy detector principle)
- Light sensor and follow-up time infinitely variable adjustable
- Installation either at the side of the door or above in a fixing height between 1.10 m and 2.20 m
- Surface mount installation is possible with accessory SM-socket (92141)
- **Application examples:** monitoring of public lavatories, corridors, archive rooms, conference rooms etc.
- **Coverings please order separately!**

ACCESSORY (OPTIONAL)



| Description | Colour | Part number |
|---|------------------------|-------------|
| Indoor 180-M-2C, fully fitted | pure white, RAL9010 | 92136 |
| Sensor insert for Indoor 180-M-2C-FM | – | 92661 |
| Accessory for sensor insert | | |
| Covering IP20 | pure white, RAL9010 | 92630 |
| Covering IP20 | traffic white, RAL9016 | 92631 |
| Covering IP20 | cream white, RAL1013 | 92632 |
| Covering IP20 | silver, RAL9006 | 92633 |
| Covering IP20 | anthracite, RAL7021 | 92634 |
| Covering IP54 | pure white, RAL9010 | 92139 |
| Accessory (optional) – Slaves see page 63! | | |
| LUXOMAT® IR-PD | grey | 92160 |
| LUXOMAT® IR-PD-Mini | grey | 92159 |
| SM-Socket for Indoor | pure white, RAL9010 | 92141 |

