


PD4-M-TRIO-DIM-SM/-FC





i PRODUCT INFORMATION

- Occupancy detector for two separate lighting groups and one potential-free light channel, for daylight-dependent lighting control
- One potential-free contact for HVAC
- One common detection area
- Two independent, movable light sensors
- Push button manual switching and dimming available
- Installation as Master
- Additional functions can be set via optional remote control
- Two 1-10 V interfaces for control of dimmable electronic ballasts

■ TECHNICAL DATA

- ⚡ 110-240 V AC , 50 / 60 Hz
- ⏻ ca. 0.6W
- 🌀 360°
- ⊘ 24 m across
- ⊘ 8 m towards
- ⊘ 6.4 m seated
- 📏 IP SM= IP20 FC= IP20 / Class II
- 🌡️ -25 °C to +50 °C
- 📦 Housing UV- and shock resistant polycarbonate
- 📡 IR-PD4-TRIO
- 🕒 Channel 1-3: 1 - 60min
- Channel 1 and Channel 2 (control the lighting)**
- 💡 3000 W, $\cos \varphi = 1$
- 💡 1500 VA, $\cos \varphi = 0.5$
- 🌙 10 - 2000 Lux
- 📏 1-10V 2 dim outputs 1-10 V DC, max. 50 EB's
- Channel 3 (control the lighting potential free)**
- 💡 3000 W, $\cos \varphi = 1$
- 💡 1500 VA, $\cos \varphi = 0.5$
- 🌙 10 - 2000 Lux



Description	Colour	Part number
PD4-M-TRIO-DIM-FC	white	92735
PD4-M-TRIO-DIM-SM	white	92730
Accessory (optional)		
IR-PD4-TRIO	grey	92097
Wire basket BSK (⊘ 200 x 100)	white	92199
Wire basket BSK (⊘ 164 x 143)	white	92467
Socket IP54 for PD4-TRIO-SM	white	92386