

PD4-DALISYS-C



white, Part No. 93378



white, Part No. 93370

Product Information

- Wide motion detection range DALI multisensor designed for corridors
- Seamless integration in B.E.G. LUXOMAT®net DALISYS
- Multimaster-capable with Slave function
- Semi-automatic, full-automatic or twilight switch
- Integrated daylight harvesting circuit (or switch output)
- Guided Light, Soft-Start PLUS, Orientation light PLUS
- DIP- and HEX-switch for quick commissioning with basic functionality
- Works out-of-the box for easy installation check
- Full range of functions can only be activated with other products of the product group B.E.G. LUXOMAT®net DALISYS
- There are markings for adjusting the detector

Technical Data

Voltage :	10 - 22 V DC via DALI Bus
Dimensions:	SM= Ø 98 x 96 mm FC= Ø 103 x 76 mm
Settings:	via DIP switch, HEX switch, B.E.G. BLE App, B.E.G. PC Tools, B.E.G. DALI Router
typ. power input :	7 mA
Detection area :	vertical 360°
Range :	max. Ø 40 m across max. Ø 20 m towards

Monitored surface, when the detector is mounted at the recommended height and for tangential approach :	250 m ²
Mounting height min./max./recommended:	2.4 m / 2.6 m / 2.5 m
Degree / class of protection :	SM= IP54 / Class II FC= IP20 / Class II
Ambient temperature :	-25 °C to +50 °C
Housing :	Polycarbonate, UV-resistant
Follow-up time :	1 sec - 2 h
Orientation light :	5 - 100 % / 1 min - 120 min / ∞
Brightness set value :	5 - 1200 Lux

Description

Description	Colour	Part number	EAN number
PD4-DALISYS-C-FC	white	93378	4007529933785
PD4-DALISYS-C-SM	white	93370	4007529933709

Accessory

Description	Colour	Part number	EAN number
PS-DALISYS-USB-REG	white	92843	4007529928439
ROUTER-DALISYS-REG	white	92850	4007529928507
PBM-DALISYS-4W	white	92842	4007529928422
