
## LUXOMAT® Indoor 180-SC



REG







ACCESSORY (OPTIONAL)

## TECHNICAL DATA

$\overline{\mathbf{c}}$	Power supply via staircase switch (230 V)
٨	▽ 180°
	max. 10.00 m

- IP I IP20 / Class II / CE
- L87 x W87 x D61 mm
  - -25°C to +50°C
    - UV- and shock-resistant Polycarbonate
  - max. 200 mA / 230 V

Ø

- Impulse duration: 0.1sec. Suppression of light level threshold: 1 min. - 10 min.
- ( 🔆 5 2000 Lux

1.10 - 2.20 m

1 Walking towards

2 Walking across

## 

## *i* PRODUCT INFORMATION

- Motion detector as wall switch LUXOMAT<sup>®</sup> Indoor 180-SC-FM with 180° detection for control of staircase switches
- Combinable with coverings in five different colours
- For the combination with switches of leading manufacturers the enclosed additional intermediate frame be used
- Light sensor and follow-up time infinitely variable adjustable
- Installation either at the side of the door or above in a fixing height between 1.10 m and 2.20 m
- Triac version in 2-conductor engineering, without neutral conductor, for operation with staircase switches
- Surface mount installation is possible with accessory of SM-socket (92141)
- The detection area can be altered by using the included blinds at the bottom of the detector
- Application examples: monitoring of staircases, long corridors – simply replace the button
- Coverings please order separately!

 $\bigcirc$ 

Л



Covering IP20 traffic white, RAL9016 92631 Covering IP20 92632 cream white, RAL1013 silver, RAL9006 Covering IP20 92633 Covering IP20 anthracite, RAL7021 92634 Covering IP54 pure white, RAL9010 92139 Accessory (optional) SM-Socket for Indoor pure white, RAL9010 92141 Stair light switch SCT1 white 92655